



Class 6 Emulating Indicator, Triple Indicators, 134 °C – 7 min.

Ref Code: C-1007

Product Description

Class 6 Emulating Indicators are cycle verification indicators that confirm the presence or absence of specific time and temperature parameters during a cycle and integrate all the critical parameters of the steam sterilization cycle. Emulating indicators can be placed inside each pack or pouch during sterilization of supplies or equipment in a validated pre-vacuum cycle. These emulating indicators can be used for routine monitoring of steam sterilization cycles. The indicators color transition from pink to dark brown/black.

Physical Parameters

Process	Steam
Dimensions	2,5 cm x 6,5 cm
Packaging	250 indicators / pack
Chemical Indicator	Initial color: Pink Signal color: Dark brown / Black %100 Toxic Heavy Metals Free

Intended Use

The indicators are for use in all Steam sterilization processes.

Class 6/Type 6 Process Indicator Requirements



- 134 °C 7 min. – 121 °C 15 min.

Instructions for Use

Use an indicator on each item, pack, peel pouch, or tray intended for steam sterilization. Place at a location considered most challenging for the steam penetration.

Process the packages/items as instructed in the sterilizer validation or manual. Upon exposure, the indicator will transition from pink to dark brown/black. The transition color may vary depending on the load configuration, length and conditions of exposure. A color transition from pink to a shade of dark brown/black provides indication of exposure. If the signal color is not achieved immediately following exposure, allow the indicator to aerate for 1 minute. If the signal color is still not achieved, this suggests ideal sterilization conditions may not have been met.

Performance Characteristics

Results Availability:	Immediately following exposure to Steam processes.
Unexposed*	Exposed to 134°C 7 min. – 121 °C 15 min. *
	

Potential Fail Color



*Colors shown are representations of printed ink initial and signal colors but may vary from actual use.

TDS-1007-1 / Rev.00 / 09-2021










The signal color achieved from exposure to steam may vary from the example above due to differences in processing parameters (i.e. load content, cycle time, temperature, etc.). For a Type 6 Process Indicator, any color change produced during exposure to steam which is close to signal color is considered acceptable.

Compliance

ISO 11140-1:2014 Sterilization of health care products – Chemical Indicators

ISO 13485:2016 Medical devices - Quality management systems

Storage and Shelf Life

	Do not reuse		Keep dry
	4°C to 30°C		Keep away from sunlight
	10% - 40% RH		Shelf life 4 years from the date of manufacture
	<p>Keep away from sterilants.</p> <p>Do not use damaged Indicators or Indicators which have transitioned to green. Do not use after expiration date.</p> <p>Do not expose this product to Dry Heat, EO, H2O2 or any sterilization processes other than Steam,</p>		

Disposal

Discard as general waste.